11 EXITING FROM, AND SOLVING PROBLEMS IN, $\mathcal{AIPS}$

This chapter contains a grab-bag of miscellaneous advice on exiting from $\mathcal{AIPS}$ and on solving a variety of common problems that may arise. The latter are also addressed in § Z.1.5.

11.1 Helping the $\mathcal{AIPS}$ programmers

Comments, suggestions and bug reports about any facet of $\mathcal{AIPS}$ are very useful to the $\mathcal{AIPS}$ programming and management group. Note that "gripes" are only useful when they are informative — *e.g.*, giving details of the circumstances under which a task failed with accompanying system error messages (if any). Terse gripes along the lines of "UVCOP doesn't work!" whilst perhaps true in some circumstances, are unlikely to arouse the $\mathcal{AIPS}$ programmers' enthusiasm. In many cases, it may be necessary for the programmer to use your data to fix the bug. A FITS-disk file read over the net is a common means to this end. The $\mathcal{AIPS}$ group may often seem unresponsive to your gripe. This is an unavoidable consequence of the breadth of the $\mathcal{AIPS}$ project combined with the small size of the group. Nonetheless, if you do not tell the programmers that there is a problem or a good idea, then you are almost certain to encounter the same problem years later and never to see your good idea put into practise. The $\mathcal{AIPS}$ group depends on help from users.

Gripes can be entered into a site-wide "`GR`" file and automatically mailed to `aipsmail@nrao.edu` (as of the `15JAN96` release) by typing:

> GRIPE $^{C}_{R}$

while in `AIPS`. Follow the directions to record your comment. Current gripes in the file may be read via

> GRINDEX $^{C}_{R}$ — to display an index of all gripes in the file.

> JOBNUM n ; GRLIST $^{C}_{R}$ — to list the n^{th} gripe in the file.

and a gripe may be deleted with

> JOBNUM n ; GRDROP $^{C}_{R}$ — to delete the n^{th} gripe in the file and notify `aipsmail`.

Note that the deleted gripe has already been e-mailed to Charlottesville, so dropped ones get sent too. Do not do a `GRDROP` unless you realize that the gripe was erroneous. (An explanatory "gripe" would be appreciated.) If you change your mind about a gripe before you finish it, type `_forget` or `_FORGET` (case sensitive!) to stop the gripe before it is mailed and entered in the file. The addition of automatic e-mail gives immediacy to all gripes and provides, for the first time, real access to the gripe system for sites outside of the NRAO. There is a data base of older gripes available via the World-Wide Web (use URL `http://info.cv.nrao.edu/aips/aips-home.html`) with an `emacs` interface.

11.2 Exiting from $\mathcal{AIPS}$

Before ending a period of data reduction with $\mathcal{AIPS}$, you should back up those data files which you wish to keep, delete all of your disk data files, tidy up your work area, and then issue the `EXIT` command to the `AIPS` program. Of course, if the computer and disks are part of your very own workstation in your office, you may ignore all this advice. The tape back-ups are a very good idea in any case. Disk files are easily deleted due to software or user malfunction, or lost due to disk hardware malfunction.

11.2.1 Backups

While processing and particularly just before exiting from *AIPS*, please delete as many of your own data sets as possible. Images and *uv* data may be backed up on tape in FITS format using the task FITTP. This task can write more than one *AIPS* file on tape in a single execution. For example, to backup all sorted *uv* files (class UVSRT), type

> TASK 'FITTP' ; INP $^{C}_{R}$	to review the inputs.
> DOALL TRUE $^{C}_{R}$	to specify that all files with the allowed name parameters are to be written.
> CLRNAME $^{C}_{R}$	to allow any name, class sequence number and disk.
> INTYP 'UV' $^{C}_{R}$	to restrict to *uv* files.
> INCLASS 'UVSRT' $^{C}_{R}$	to restrict to class UVSRT files.
> INP $^{C}_{R}$	to check the inputs.
> GO $^{C}_{R}$	to write the tape.

Then, for example, to write all 3C123 files on disk 2 after the sorted *uv* data files, type:

> INTYP ' ' ; INCLASS ' ' $^{C}_{R}$	to allow any class and type.
> INNA '3C123' ; INDISK 2 $^{C}_{R}$	to restrict things to 3C123 files on disk 2.
> WAIT ; GO $^{C}_{R}$	to have AIPS wait for the FITTP execution started above to finish and then to run FITTP with the new inputs.

Note that this sequence will write two copies of any 3C123 UVSRT files to be found on disk 2.

11.2.2 Deleting your data

Please delete redundant images and data as soon as possible to preserve disk space for yourself and other users. It is tempting to work on many sets of data at the same time, but this generally takes a lot of disk space and users should limit the amount of data resident on disk to that which will be processed during the session. A data set and all extension files can be deleted by:

> IND *n* ; GETN *ctn* $^{C}_{R}$	where *n* and *ctn* select the disk and catalog numbers of the data set to be deleted.
> ZAP $^{C}_{R}$	to do the deletion.

To delete data in contiguous slots from *n* to *m* in a catalog, set the INDISK and use the loop:

> FOR I = *n* TO *m* ; GETN I ; ZAP ; END $^{C}_{R}$

For massive deletions — the kind we hope you will use when you leave an NRAO site — use:

> ALLDEST $^{C}_{R}$	to destroy all data files consistent with the inputs to ALLDEST.

And to compress your message file, after using PRTMSG to print any you want to keep, use:

> PRNUM -1 ; PRTASK ' ' ; PRTIME 0 $^{C}_{R}$	to do all messages.
> CLRMSG $^{C}_{R}$	to do the clear and compress.

The verb TIMDEST may be used to delete old data and messages belonging to all users (including you) having data in your *AIPS* data areas. The minimum definition of "old" is set by your local *AIPS* Manager, but you may start with a more forgiving definition (with the DETIME adverb). The TIMDEST limits for each disk are normally shown by the FREESPAC verb. DO NOT USE ANY OTHER METHOD TO DELETE OTHER USERS' DATA OR MESSAGES WITHOUT THE EXPLICIT PERMISSION EITHER OF THE OTHER USER OR OF THE AIPS MANAGER.

11.2.3 Exiting

To exit from AIPS type:

> EXIT $^{C}_{R}$ to leave TV, message, and graphics servers running, or

> KLEENEX $^{C}_{R}$ to kill server processes as well as AIPS.

Please clean up any papers, tapes, etc. in the area around your terminal before you go.

11.3 Solving problems in using *AIPS*

On all computer systems things go wrong due to user error, program error, or hardware failure. Unfortunately, *AIPS* is not immune to this. The section below reviews several general problem areas and their generalized solutions. Refer to § Z.1.5 for the details appropriate to NRAO's computer systems. Some well-known possibilities follow.

11.3.1 "Terminal" problems

If your workstation window is alive, but AIPS has "disappeared" you may have "suspended" it by typing CTRL Z. The AIPS can be left in a suspended state, placed into the "background" with bg, or returned to the "foreground" again with fg after which it will resume accepting terminal input. If your *AIPS* appears to be "suspended", try typing jobs to see which jobs are attached to your window and then use fg %*n* to bring back job *n* where *n* is the job number of the suspended AIPS. If no *AIPS* job is suspended from the current window, check all other windows you have running on the workstation for the missing simian before starting a new AIPS. Otherwise, you may run out of allowed AIPSes and/or encounter mysterious file locking problems.

If your workstation window (or terminal on obsolete systems) is "dead", *i.e.*, refuses to show signs of talking to your computer, you have a problem. There are numerous possible causes. If typed characters are shown on the screen, but not executed, then

1. Are you executing a long verb, *e.g.*, TIMDEST, REWIND, AVFILE, RESCALE? If so, be patient.
2. Are you executing some interactive TV or TEK verb which is waiting for input from the cursor or buttons? If so, provide the input.
3. Have you started a task with DOWAIT set to TRUE (+1.0)? If so, wait for the task to finish. Most tasks report their progress on the message monitor window (or your input window).
4. Is AIPS waiting while a tape rewinds or skips files or is it waiting to open some disk file currently being used by one of your tasks? Be patient.

If typed characters do not appear, then

1. Have you stopped output to your window accidentally by hitting the appropriate NO SCRL or other XOFF control sequence? If so, hit the XON control sequence. (These are CTRL S and CTRL Q, respectively.)
2. Do other windows connected to the computer appear to be "alive"? If so, use one of them and inquire about the status of your AIPS program and tasks; on Berkeley Unix try ps aux $^{C}_{R}$ and on Solaris and other Bell Unix try ps -elf $^{C}_{R}$. It might be necessary to stop your old AIPS session from your new window and then use that window to start a new AIPS.

3. Can you abort `AIPS` at your window using the appropriate system commands (*i.e.*, `CTRL C` on Unix machines)?

4. If all windows appear dead, then your computer or its X-Windows server may have "crashed." Try a remote login from another computer. If that works, check on your processes and try to kill the server and other tasks. This should return your computer to a login state. Otherwise, report the problem to your *AIPS* Manager or System Administrator. If you feel you must reboot the system, do so *only* after checking that all current users and the System Administrator (if available) agree that that action is required.

5. If even a reboot fails, report the problem to the System Administrator or hardware experts and go do something else. UNDER NO CIRCUMSTANCES SHOULD YOU ATTEMPT TO REPAIR ANY HARDWARE DEVICES. Such repairs must be performed by trained personnel.

11.3.2 Disk data problems

If you encounter the message `CATOPN: ACCESS DENIED TO DISK` *n* `FOR USER` *mmm*, it means that user *mmm* has not been given access to write (or read) on limited-access disk *n*. The access rights for all disks can be checked by typing `FREESPAC` in the `AIPS` session. In the list of mounted disks, the `Access` column can say `Alluser`, `Scratch` (scratch files only), `Resrved` (limited access including you), and `Not you` (limited access not including you). If you feel that you should have access to that particular disk, resume using your correct user number or see your *AIPS* Manager about enabling your user number.

If your data set seems to have disappeared, consider

1. Have you set `INDISK` *et al.* (especially `INTYPE`) correctly before running `CAT`? Type `INP CAT` $^{C}_{R}$ to check. Is `USERID` not set to 0 or your user number?

2. Are you connected to the right *AIPS* computer, if your site has more than one?

3. Are the desired disks mounted for your `AIPS` session? Type `FREE` $^{C}_{R}$ to see which disks are currently running and which numbers they are assigned in this session. When you attach disks from other computers (using the `da=` option of the `aips` command — § 2.2.3), they are assigned numbers which depend on the list of computers and which may thus vary from session to session.

4. Did you leave your file untouched for a "long" time on a public disk? Other users and system managers often run `TIMDEST` to delete "old" files to make room for new ones. In this case your data are gone and we hope you made a backup on tape.

The message `write failed, file system is full` will appear when the search for scratch space encounters a disk or disks without enough space. (*AIPS* usually emits messages at this time as well.) This is only a problem when none of the disks available for scratch files has enough space, at which point the task will "die of unnatural causes." Run the verb `FREESPAC` to see how much disk is available and then review the inputs to the task to make sure that `OUTDISK` and `BADDISK` are set properly. Change them to include disks with space. Check the other adverbs to make sure that you have not requested something silly, such as a 2000-channel cube 8096 on a side. Then try again.

If there simply is not enough space, try some of the things suggested in § 3.6, such as `SCRD` to delete orphan scratch files, `TIMDEST` to delete "old" files, `DISKU` to find the disk hogs, and, if all else fails, `ZAP` to delete some of your own files. Your *AIPS* Manager may help you by removing non-*AIPS* files from the *AIPS* data disks. Do not do this yourself unless they are your files.

11.3.3 Printer problems

All AIPS print operations now function by writing the output to a disk text file, then queueing the file to a printer, and then sometime later, deleting the file. After the job is queued, the AIPS task or verb will display information about the state of the queue. Read this carefully to be sure that the operation was successful and to find out the job number assigned to your print out. If you are concerned that your print job may be lengthy, or expect that you will only need a few numbers from the job, please consider using the `DOCRT` option to look at the display on your terminal or the `OUTPRINT` option to send the display to a file of your choosing without the automatic printing. See § Z.1.5.3. for information about printing such files later.

To find out what jobs are in the spooling queue for the relevant printer, type, at the monitor level:

`$ lpq -P`*ppp* $^{C}_{R}$ to show printer *ppp*.

`$ lpstat` *ppp* $^{C}_{R}$ to show printer *ppp* under Solaris, HP, SGI (Sys V systems).

where *ppp* is the name of the printer assigned to you when you began `AIPS`. If the file is still in the queue as job number *nn*, you can type simply

`$ lprm -P`*ppp nn* $^{C}_{R}$ to remove the job.

`$ cancel` *nn* $^{C}_{R}$ to remove the job under Sys V systems.

`lprm` and `cancel` will announce the names of any files that they remove and are silent if there are no jobs in the queue which match the request.

Since modern printers are capable of swallowing large amounts of input, your job may still be printing even though it is no longer visible in the queue. If you turn off the printer at this stage, you are likely to kill the remainder of your print job and quite possibly one or more other print jobs that followed yours. Use discretion. Do not turn the printer back on if the job is still in the queue. Most systems will start the print job over again after you turn the power back on without doing a `lprm` or `cancel`.

If your printout fails to appear

1. Did the print queueing actually work? Review the messages at the end of the verb or task.
2. Did the printout go to a printer other than the one you expected? Was it diverted to a printer used for especially long print jobs or one used for color plots? The messages at the end of the verb or task should show this.
3. Was the printer not working or backed up for so long that the file was deleted before it could be printed? The delay time for deletion is shown at the end of the verb or task. It can be changed by your AIPS Manager for future jobs.
4. Was your print job, or that of a user in the queue ahead of you, a large plot? These can take a long time in some PostScript printers (usually indicated by a blinking green light), so be patient.

11.3.4 Tape problems

When `AIPS` does a software `MOUNT` of a magnetic tape, it actually reads the device on most systems. An error messages along the lines of `ZMOUN2: Couldn't open tape device` ... usually means that you have attempted the `MOUNT` before the device was ready. Wait for all whirring noises and blinking lights to subside and try again. Remote tape mounts are more fragile. If you get a message such as `ZVTPO2 connect (INET): Connection refused`, then the tape dæmon `TPMON` is probably not running on the remote host. `EXIT` and restart `AIPS`, specifying the remote host in the `tp=` option (see § 2.2.3). If you are told `AMOUNT: TAPE IS ALREADY MOUNTED BY TPMON`, then there is a chance that you are trying to mount the wrong tape or that someone left the tape device in a mounted state. See § Z.1.5.7 for advice on curing this stand-off between `AIPS`, which knows that the tape is not mounted, and `TPMON` which knows that it is.

If you are having problems reading and writing a tape, consider

1. Did you actually mount the tape in software from the *AIPS* level with the `MOUNT` verb. A message like `ZTPOPN: NO SUCH LOGICAL DEVICE = AMT0`*n*`:` indicates that you have not.
2. Have you specified the `INTAPE` or `OUTTAPE` number to correspond with the drive you mounted the tape on?
3. Does your computer have access to tapes on the remote host? The message `AIPS TAPE PERMISSION DENIED ON REMOTE HOST` suggests not. See the *AIPS* Manager for the remote host.
4. Is the tape correctly loaded in the drive and is the drive "on line" (check the `ON LINE` light)?
5. Have you set the density correctly? Some drives need the density to be set by a switch, others have software control. Some try to read the tape and sense the density automatically. Be aware that some drives do not set the density until you actually read or write the tape. Under these circumstances, the density indication on the drive can be misleading. If in doubt, consult your local *AIPS* Manager about the meaning of the tape density indicator lights on the drive you are using.
6. Are you using the correct program to read the tape? If you are unsure of the format of a tape, use the task `PRTTP` to diagnose it for you. It will recognize any format that *AIPS* is able to read.
7. Are you writing to a completely blank tape? This fails sometimes. Or are you writing to an old tape which is new to you? In both cases, try specifying `DOEOT FALSE` $^{C}_{R}$ and then rerunning the tape-writing program.
8. Has the drive been cleaned recently? Do *not* attempt to clean a drive yourself. Using the wrong cleaning fluid or cleaning the wrong parts of a drive can do serious damage. If you have any doubts, use another drive.
9. Is your tape defective? Tapes can lose oxide or become stretched, creased, or dirty, all of which will cause problems. Try using another tape, if possible.

11.4 Additional recipes

11.4.1 Banana coffeelate

1. Peel and mash 2 ripe `bananas`.
2. Blend in 1/2 teaspoon `vanilla extract`, a few grains `salt`, 1/4 cup `chocolate syrup`, 2 teaspoons `sugar`, and 2 teaspoons instant powdered `coffee`.
3. Add $1\frac{1}{2}$ cups `milk`.
4. Beat with rotary beater or electric mixer until smooth and creamy. Chill.

11.4.2 Banana pick-me-up

1. Slice ripe, peeled `bananas` into 3 cm chunks.
2. Wrap each chunk in strip blanched `bacon`.
3. Prepare mixture of `brown sugar` and `cinnamon` to taste.
4. Sprinkle mixture over banana chunks.
5. Bake at 350 deg until the bacon is crisp and the sugar slightly caramelized.